

09/656563

A PAPERMAKING DEVICE FOR PRODUCING A MULTILAYER LINER
AND ASSOCIATED METHODS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No.
60/169,557, filed December 8, 1999.

FIELD OF THE INVENTION

The present invention relates to a method for the production of a liner comprising at least a top layer and a base layer, wherein a forming section with at least two forming units is used to create a fiber web, said fiber web being conveyed through a press section and further to a drying section, said press section comprising a number of roll nips and at least one impermeable transfer belt with at least one smooth surface. The invention also relates to a paper machine for realization of the method.

BACKGROUND OF THE INVENTION

A liner, a form of multilayer board, comprises frequently a top layer, which is intended for printing. This top layer must display a high smoothness in order to achieve good printability. For production of the surface layer, bleached pulp is preferably used, more particularly, pulp which is bleached to high brightness and which contains short fibers.

Different methods and machines for the production of multilayer board are described in a number of different documents in the patent literature, e.g., EP 1 076 606, US 5 681 431, US 5 178 732, EP 0 511 186, WO 92/06242, US 4 961 824, EP 0 511 185, US 5 074 964, EP 0 233 058 and SE 506 611. However, none of these documents teach how to produce multilayer board, i.e. a liner, wherein a layer intended for printing can

acquire a very good printability in a high speed process.

SUMMARY OF THE INVENTION

5 The above and other needs are met by the present invention which, in one embodiment, provides a method for the production of a liner comprising at least a top layer and a base layer. A forming section is provided, having at least two forming units to create a fiber web. A press section is provided, comprising a number of rolls and a transfer belt with at least one smooth surface, wherein at least some of said rolls form roll nips comprising a last roll nip for conveying said fiber web through the press section and
10 further to a drying section. By moving said transfer belt through the last nip in the press section, the fiber web is conveyed through the last nip of the press section in such a manner that the layer intended for printing of the web is pressed against said smooth surface of the transfer belt. In this manner, the layer intended for printing acquires a very good printability, wherein the fiber web is simultaneously transferred through the press
15 section at a relatively higher speed.

In accordance with further aspects of the method:

- the fiber web is exposed to a liner load of between 600-2000 KN/m in said last nip,
- 20 - the fiber web **W** is conveyed through at least three nips in the press section and the fiber web **W** in the next-to-last nip is exposed to a linear load of between 30-150 KN/m,
- the fiber web **W**, before the next-to-last nip, is conveyed through a leading nip which consists of a shoe press and under a linear load of between 200-1000 kN/m,
- 25 - the fiber web **W**, before the next-to-last nip, is conveyed through a leading nip which consists of a press and under a linear load of between 50-200 kN/m,
- the base layer is formed of unbleached pulp which is substantially long-fibered and preferably contains fir and/or pine fibers and the top layer is formed of a pulp, which at least partially contains short fibers such as birch or eucalyptus fibers,
- 30 wherein the pulp for the top layer is also preferably bleached.
- the grammage of the completed liner is 60-205 g/m², preferably 60-150 g/m².

- the fiber web **W** is conveyed through the press section **P** at a speed of 750-2000 m/min, preferably exceeding 1000 m/min, more preferably exceeding 1200 m/min,

- the layer intended for printing consists of bleached pulp,

5 - the layer intended for printing contains at least 30 weight-% of short fibers,

- the layer intended for printing contains at least 50 weight-% of short fibers.

- the layer intended for printing is formed on top of the base layer in the forming section, so that layer intended for printing of the fiber web constitutes the upper layer of the web **W**.

10

Embodiments of the invention also relate to a paper machine for production of a liner, comprising a forming section and a press section, said forming section comprising at least two forming units in order to permit production of a fiber web with at least two layers of which one layer constitutes a top layer, said press section comprising a plurality
15 of rolls and a transfer belt with at least one smooth surface, wherein at least some of said rolls form roll nips comprising a last nip, wherein said last nip is through-fed by said transfer belt and arranged such that its smooth surface is directed against the layer intended for printing of the fiber web when the fiber web runs through said last nip.

20

In accordance with further aspects of the paper machine:

- the smooth surface of the transfer belt is directed away from an upper press roll in said last nip, said last nip preferably comprising a shoe press unit;

- the press section comprises at least three nips, wherein preferably the next-to-last nip consists of a press,

25

- said three nips are achieved with four roll units,

- said three nips are achieved with five roll units, wherein preferably the first of said three nips comprises a shoe press,

- said transfer belt is impermeable.

30

Further, the invention relates to a method for production of a liner comprising at least one layer of bleached pulp and one layer of unbleached pulp. A forming section is

provided, having at least two forming units to create a fiber web. A press section is provided, comprising a number of rolls and one transfer belt with at least one smooth surface, wherein at least some of said rolls form roll nips comprising a last nip for conveying said fiber web through the press section and further to a drying section,
5 wherein said transfer belt is moved through said last nip of the press section in such a manner that the layer of bleached pulp is pressed against said smooth surface of the transfer belt.

Finally, the invention relates to a method for production of a liner comprising at
10 least one layer of pulp containing at least 30 weight-% of short fibers and one layer of pulp containing essentially long fibers. A forming section is provided, having at least two forming units for creating a fiber web. A press section is provided, comprising a number of rolls and one transfer belt with at least one smooth surface, wherein at least
15 some of said rolls form roll nips comprising a last nip for conveying said fiber web through the press section and further to a drying section, wherein said transfer belt runs through the last nip in the press section and the fiber web is conveyed through the last nip in the press section in such manner that the layer consisting of at least 30 weight-% of short fiber pulp is pressed against said smooth surface of the transfer belt.

20 BRIEF DESCRIPTION OF THE DRAWINGS

Having thus described the invention in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

Fig. 1 is a schematic representation of a forming section and a press section in accordance with one embodiment of the invention.

25 **Fig. 2** is a schematic representation of a press section according to an alternate embodiment of the invention.

Fig. 3 is a schematic representation of a forming section and a press section according to another alternate embodiment of the invention.

Fig. 4 is a schematic representation of a papermaking machine in accordance with
30 another alternate embodiment of the invention,

Fig. 5 is a schematic representation of a papermaking machine in accordance with another alternate embodiment of the invention, and

Fig. 6 is a schematic representation of a papermaking machine in accordance with another alternate embodiment of the invention.

5

DETAILED DESCRIPTION OF THE INVENTION

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should
10 not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

Fig. 1 shows one embodiment in accordance with the invention. A forming
15 section **1** is illustrated. The forming section **1** consists of a fourdrinier wire, with two forming units comprising a first **1A** and a second **1B** headbox. The construction shown is known to one skilled in the art and is therefore not described in detail. By the forming section **1**, a fiber web **W** is created, which consists of a base layer and a top layer. After
20 the forming section **1**, the fiber web **W** is conveyed into a press section **P**, by being transferred onto a first press felt **2** with a pick-up suction roll **3**. The press section comprises three roll nips, which are formed by only four rolls **6, 7, 9, 11**, whereby a compact arrangement can be achieved. To be able to optimize the overall height of the section, the rolls are suitably placed, somewhat laterally in relation to each other, so as to
25 be placed in the proximity to an oblique (non-vertical) line. (see also **Fig. 3**) The press felt **2** runs from the pick-up suction roll **3** to a press roll **7** (suitably a suction roll) and then around guide rolls (not shown). The suction roll **7** constitutes the upper roll in a first nip which is achieved between the suction roll **7** and a second press roll **6** placed towards the bottom. The press roll **6** cooperates with a lower press felt **5**, which cooperates with
30 two guide rolls, **4, 8**. Consequently, a double-felted nip is created between the first two press rolls **6, 7**. A second nip is created between the first suction roll **7** and a third press

roll 9. The second nip is also double-felted, in that a third press felt 19 runs around the third press roll 9.

Finally, a third roll nip is shown, between the third press roll 9 and a shoe press roll 11. Apart from the third felt 19, one impermeable transfer belt 30 is fed through the third nip. The transfer belt 30 has at least one smooth surface 30A, which is configured to turn away from the shoe press unit 11 and against the third press felt 19. The transfer belt 30 passes a first guide roll 10 before the nip and around a second guide roll 12 after the nip. Immediately before (seen in the machine direction) the second guide roll 12, a fourth felt 14 (or drying wire), which runs around a suction roll 13 and a guide roll 15, abuts the bottom side of 30A of the transfer belt 30. Thereafter, a drying section D follows, which is only partially shown. A drying wire 16, a vacuum roll 17 and a drying cylinder 18 are also shown. The vacuum roll 17 is arranged so that the drying wire 16 runs against the felt 14 between the suction roll 13 and the guide roll 15.

The above-described device is, in accordance with embodiments of the invention, intended to manufacture, with high efficiency, a multilayer liner having a top layer with high printability. The described device operates in the following manner. A base layer is applied on the fourdrinier wire by a first headbox 1A. Thereafter, a top layer is spread (in a known manner) by a second headbox 1B. The base layer consists essentially of pulp containing long fibers, preferably containing fir and/or pine fibers. The top layer is suitably formed by a pulp, which at least partially contains short fibers. (It will be understood that the determinations regarding the weight-% of fibers, which are mentioned, relates to the end product.) In most applications, fibers from easily bleached kinds of wood, such as birch or eucalyptus, are preferably used for the top layer, which are bleached to a relatively high brightness, preferably over 85 ISO, more preferably to a brightness exceeding 90 ISO. The formed fiber web W is then fed over to the press section P with a pick-up suction roll 3 and the felt 2 that runs therearound. Consequently, the top layer abuts against the felt 2. The base layer then meets the lower press felt 5 and the fiber web w is fed through the first roll nip 6, 7 which is accordingly double-felted. The fiber web then follows the felt 2 around the first suction roll 7 into the second roll nip

7, 9. In the second roll nip, the top layer abuts against the press felt 2, while the base layer abuts against a third smoother press felt 19. The web thereafter follows the smoother third press felt 19, around a third press roll 9, which preferably consists of a grooved roll. The web then runs into the third roll nip 9, 11 in which the top layer meets the smooth surface 30A of the impermeable transfer belt 30. The web follows the impermeable transfer belt 30 until it encounters the drying wire/felt 14 which runs around the suction roll 13. The web then follows the felt 14 until it encounters the drying wire 16 and the web thereafter follows the drying wire 16 around the vacuum roll 17 to a drying cylinder 18 and further into the drying section D.

10

In Fig. 2, an alternate embodiment of the invention is shown. This embodiment is similar to the embodiment shown in Fig. 1, and therefore just the variations will be described. According to this embodiment, five rolls are used to create the three nips, instead of four rolls as shown in Fig. 1, which allows larger flexibility for the set of rolls. As shown, the first roll nip is created with a shoe press roll 21 which presses against a lower press roll 6. A suction press roll 23 follows thereafter, which constitutes the second nip with the next-to-last press roll 9. A guide roll 22 is arranged above the press roll 23 in order to convey the felt 2. The lower press felt 5 runs, as previously described, through the first roll nip and around the press roll 23. In this embodiment, the transfer belt 30 runs around the next-to-last press roll 9. As in Fig. 1, the last press unit 11 is formed with a shoe press roll. A press felt 19 runs around the shoe press roll 11 as guided by guide rolls 24, 25. In accordance with Fig. 1, the top layer abuts the upper press felt 2 in the first nip 6, 21, and is thereafter separated from the press felt 2 with the suction roll 23. The web may also be separated from the upper press felt 2 directly after the first nip since the guide roll 22 is preferably movably arranged, whereby the web W may be allowed to run towards the second nip in contact only with the lower press felt 5. In the second nip 23, 9, the top layer encounters the smooth surface 30A of the transfer belt 30 and thereafter follows the transfer belt 30 around the next-to-last press roll 9 and through the last nip 9, 11. Thereafter, as in Fig. 1, the web is transferred to a drying wire/felt 14 which runs toward the drying section D. Consequently, the top layer is also pressed in the last nip against the smooth surface 30A of the transfer belt.

In **Fig. 3**, a further embodiment in accordance with the invention is shown. In contrast to the embodiments shown in **Figs. 1 and 2**, a twin wire former with a first **1A** and a second **1B** headbox is used for creating a web **W** with a top layer and a base layer.

5 In accordance with **Fig. 1**, the press section is formed of only four press rolls. The first roll nip consists of a first press roll **21** and a suction roll **6**. In accordance with **Fig. 2**, the transfer belt **30** runs around the next-to-last press roll **9** in order to form both the next-to-last nip **6, 9** and the last nip **9, 11**. In addition, the last press unit comprises a shoe press roll **11**. Also, as in **Fig. 1** and **Fig. 2**, the web is transferred from the transfer belt **30** to a

10 drying wire/felt **14** as shown in **Fig. 3**, over a suction roll **13**, and then to a drying wire (not shown).

In **Fig. 4**, still another embodiment in accordance with the invention is shown wherein only two roll nips are used. The forming section **1** is similar to that shown in

15 **Figs. 1 and 2**. Also, the transferring of the web from forming section **1** to drying section **D** is substantially similar to that previously described herein. The first nip **6, 21** is substantially similar to the configuration shown in **Fig. 2**, except that the lower press felt **5** in **Fig. 4** runs only through one roll nip and the upper press felt **2** preferably consists of a smooth felt. The first nip **6, 21** can, however, also comprise a press. In the last roll nip

20 **9, 11**, in a similar manner to the earlier shown embodiments, the top layer of the web encounters the smooth surface **30A** of the transfer belt **30**. The web **W** is then transferred in a known manner with a suction roll **24** from the upper felt **2** to the third press felt **19**, before being conveyed into the last nip **9, 11**.

25 In **Fig. 5** there is shown a further embodiment according to the invention. In **Fig. 5**, the main portion of the press section **P** is similar to the press section shown in **Fig. 2**. The transfer zone from the press section to the drying section **D** of **Fig. 5** is similar to that shown in **Fig. 4**. The variation of the embodiment shown in **Fig. 5** comprises the arrangement of another press roll nip **6', 21'** at the beginning of the press

30 section **P**. As shown, the fiber web **W** is transferred from the forming section **1** to the press section **P** by a press felt **2'** and a suction pick up roll **3'**, which conveys the web on

to the press felt 2'. Thereafter, the web **W** encounters a second press felt 5' from below, such that a double-felted nip is created between the first pairs of rolls 6', 21' forming the first roll nip. As shown in Fig. 5, the first nip is a press roll nip without a shoe press roll. The web **W** then follows the lower press felt 5' into contact with a suction roll 3, which
5 transfers the web **W** onto a third press felt 2. Thereafter, the press section is similar to that shown in Fig. 2 and, accordingly, is not described in detail. However, it should also be noted that this press section, including four roll nips, is configured such that the top layer of the web is pressed against the smooth surface 30A of the transfer belt in the last nip.

10

The invention is not limited to what is described herein, but can be varied within the scope of the following claims. Consequently, it will be understood that, for instance, more than four roll nips can be used, if desired for certain installations. In addition, it will be understood that more arrangements of rolls may be used in accordance with the
15 invention. Further, it will be understood that a liner consisting of more than two layers can be produced by a method according to the invention, for instance triple layers, four layers, etc. wherein different mixtures of pulp can be used to manufacture desired products. It will also be understood that, in certain cases, mixtures of pulp entirely without short fibers may be preferred for the top layer. Furthermore, the top layer may be
20 formed, so as to constitute the lower layer in the fiber web, by initially applying the top layer with the first headbox 1A on the forming wire, wherein the equipment in the press section must be reversed, at least with reference to the last roll nip as shown in Fig. 6. Finally, it will be understood that the web **W** may be configured to run vertically through the last nip.

25

Moreover, it is known to one skilled in the art that the transfer belt does not have to be impermeable, even though this is normally preferred. One skilled in the art also knows that there exist several different options of impermeable transfer belts that can be used, such as, for example, a TRANSBELT™ (trademark belonging to Albany
30 International).

Many modifications and other embodiments of the invention will come to mind to one skilled in the art to which this invention pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed
5 and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000